

**GPG**

Diesel Generating Set

MODEL	GP-SC200 (S)
Prime Power (50Hz)	160kW/200kVA
Standby Power (50Hz)	176kW/220kVA



Standard Features



- GPG diesel engine made by SDEC China, Model: SC9D280D2. With radiator at ambient temperature 40°C, fans are driven by belt, with safety guard, With DC 24V charge alternator.
- GPG Alternator Model: SC274G1 single bearing alternator; IP22 Protection, Insulation class H
- Stand type control panel with many kinds of Display and Protection function is equipped
- Two 12V starter maintenance free battery.
- Power output MCCB is equipped.
- Accessory: A suit of ripple flex exhaust pipe; exhaust siphon, muffler; and a set of spare parts & Tools & Documents.



- The structure is built-up, the built-in residential muffler makes the noise lower.
- Exhaust guide plate and air channel for air intake&noise reduction are mounted within soundproof canopies.
- Outside Emergency Stop Button.
- Inside power Cathode switch.
- Outside Fuel Inlet.
- Base Fuel tank is equipped, With lifting ear and forklift slots. Outside fuel inlet/return, outside lub oil and coolant drain.
- Noise level with no loads @ 7M is 75dB(A)

Generator Ratings

Voltage (V)	Frequency (Hz)	Phases	Power Factor	Standby Current	Prime Current	Standby Power	Prime Power
			(COSφ)	(A)	(A)	(kW/kVA)	(kW/kVA)
440/254	50	3	0.8	288.6	262.4	176/220	160/200
400/230	50	3	0.8	316.8	288.0	176/220	160/200
380/220	50	3	0.8	332.6	302.4	176/220	160/200
Other	Customizing for Different Specification						

Sales Promises

- All the gensets are tested on load before they leave factory, various kinds of functions are tested . and test reports are provided.
- Warranty for all of our gensets and accessories is according to our standard conditions since testing: 12 months or 1,000 running hours accumulatively, subject to the earlier, kindly refer to our service terms.



GPG

Engine Data

Manufacturer / Model:	SDEC/SC9D280D2
Air Intake System:	4-Cycle, Turbocharger, Aftercooling
Fuel System:	Direct injection
Cylinder Arrangement:	6 cylinders Vertical in-line
Displacement:	8.82L
BorexStroke:	114x144 (mm)
Compression Ratio:	18:1
Rated RPM:	1500rpm
Max. Standby Power at Rated RPM:	204kW
Governor Type:	Electronic Speed Governer
Exhaust System	
Exhaust Flow:	35.9m ³ /min
Exhaust Temperature:	600°C
Max Back Pressure:	6kPa
Air Intake System	
Max Intake Restriction:	6kPa
Combustion air Flow:	16.4m ³ /min
Fuel System	
110% Standby Power Load:	53.6L/h
100% Prime Power Load:	48.6L/h
75% Prime Power Load:	36.2L/h
50% Prime Power Load:	24.3L/h
Oil System	
Max. sump capacity	19L
Cooling System	
Total Coolant Capacity (engine only):	12L
Thermostat operation range:	82-93°C
Electrical System	
System Voltage:	DC 24 V
Rated Current for Charge Alternator:	55 A

**GPG****Alternator Data**

Manufacturer / Type:	SDEC/ SC274G1
Number of Phase:	3
Connecting Method:	3 Phase and 4 Wires, "Y" type connecting
Number of Bearing:	1
Power Factor:	0.8
Protection Grade:	IP22
Altitude Requirement:	≤1000m
Exciter Type:	Brushless, Self-exciting
Insulation Class/Temperature Rise:	H/H
Telephone Influence Factor (TIF):	<50
THF:	<2%
Voltage Regulation, Steady State :	≤±1%
Alternator Capacity:	200kVA
Alternator Efficiencies:	93.3%

Generating Set Data

Frequency Reduce:	≤5%
Frequency Regulation, Stead State:	≤1.5%
Waveform Distortion(no load):	<1.5%
Sudden Frequency Warp (100% Sudden Reduce):	≤+12%
Sudden Frequency Warp (Sudden Increase):	≤-10%
Frequency Recovery Time (100% Sudden Reduce) :	≤5S
Frequency Recovery Time (Sudden Increase):	≤5S
Voltage Regulation:	≥±5%
Voltage Regulation, Stead State:	≤±2.5%
Voltage Modulation:	0.30%
Sudden Voltage Warp (100% Sudden Reduce):	≤+25%
Sudden Voltage Warp (100% Sudden Increase):	≤-20%
Voltage Stable Time (100% Sudden Reduce):	≤6S
Voltage Stable Time (100% Sudden Increase):	≤6S
Voltage Unbalance:	1%



GPG

Standard Control Panel



HKY-6110 control panel is fit for backpack structure and standing structure. This control panel is a panel which holds a HGM6110 made by Smartgen the professional module maker in China as its core intelligent control module. It has plenty friendly operation interface with many functions such as running parameter detecting, static, record, pre-alarm, Remote control, monitor & protection.


Options

Engine	Alternator	Control and Power Distribution System	Others
--------	------------	---------------------------------------	--------

● 50°C High Temperature Radiator	● Permanent Magnet Generator (PMG)	● ComAp Control module	● Daily Fuel Tank
● Water Separator	● Anti Condensation Heater	● Deepsea Control module	● Base Fuel Tank
● Water Jacket Heater	● Drop CT(For Paralleling)	● Auto Transfer Switch(ATS)	● Trailer Type
● Oil Heater		● Battery Charge	● Automatic Input System For Fuel
● Oil Discharging Pump		● Manual Paralleling System	● Maintenance Tools
		● Auto Paralleling System	● Accesory Bag
		● Electronic Indicator for Fuel Level	● Wind Scooper for Soundproof Canopy

Dimension & Weight

Open Type



Overall Size LxWxH

2550mm x 1050mm x 1750mm


Weight

1650 kg

Base fuel tank capacity

Full load running for 6~8 hours

Soundproof Type



Overall Size LxWxH

3300mm x 1200mm x 1850mm

Weight

2800 kg

Base fuel tank capacity

Full load running for 6~8 hours