



GPG

Diesel Generating Set

| MODEL | GP-SC450 (S) |
|----------------------|--------------|
| Prime Power (50Hz) | 360kW/450kVA |
| Standby Power (50Hz) | 400kW/500kVA |



Standard Features



- GPG diesel engine made by SDEC China, Model: SC25G610D2. With radiator at ambient temperature 40°C, fans are driven by belt, with safety guard, With DC 24V charge alternator.
- GPG Alternator Model: SC314F1 single bearing alternator; IP22 Protection, Insulation class H
- Stand type control panel with many kinds of Display and Protection function is equipped
- Two 12V starter maintenance free battery.
- Power output MCCB is equipped.
- Accessory: A suit of ripple flex exhaust pipe; exhaust siphon, muffler; and a set of spare parts & Tools & Documents.



- The structure is built-up, the built-in residential muffler makes the noise lower.
- Exhaust guide plate and air channel for air intake&noise reduction are mounted within soundproof canopies.
- Outside Emergency Stop Button.
- Inside power Cathode switch.
- Outside Fuel Inlet.
- Base Fuel tank is equipped, With lifting ear and forklift slots. Outside fuel inlet/return, outside lub oil and coolant drain.
- Noise level with no loads @ 7M is 77dB(A)

Generator Ratings

| Voltage (V) | Frequency (Hz) | Phases | Power Factor | Standby Current | Prime Current | Standby Power | Prime Power |
|----------------|---|--------|--------------|-----------------|---------------|---------------|-------------|
| | | | (COSφ) | (A) | (A) | (kW/kVA) | (kW/kVA) |
| 440/254 | 50 | 3 | 0.8 | 656.1 | 590.4 | 400/500 | 360/450 |
| 400/230 | 50 | 3 | 0.8 | 721.7 | 648.0 | 400/500 | 360/450 |
| 380/220 | 50 | 3 | 0.8 | 759.7 | 680.4 | 400/500 | 360/450 |
| Other | Customizing for Different Specification | | | | | | |

Sales Promises

- All the gensets are tested on load before they leave factory, various kinds of functions are tested . and test reports are provided.
- Warranty for all of our gensets and accessories is according to our standard conditions since testing: 12 months or 1,000 running hours accumulatively, subject to the earlier, kindly refer to our service terms.



GPG

Engine Data

| | |
|---------------------------------------|-------------------------------------|
| Manufacturer / Model: | SDEC/SC25G610D2 |
| Air Intake System: | 4-Cycle, Turbocharger, Aftercooling |
| Fuel System: | Direct injection |
| Cylinder Arrangement: | 12 cylinders V type |
| Displacement: | 25.8L |
| BorexStroke: | 135x150 (mm) |
| Compression Ratio: | 16:1 |
| Rated RPM: | 1500rpm |
| Max. Standby Power at Rated RPM: | 445kW |
| Governor Type: | Electronic Speed Governer |
| Exhaust System | |
| Exhaust Flow: | 86m ³ /min |
| Exhaust Temperature: | 650°C |
| Max Back Pressure: | 6kPa |
| Air Intake System | |
| Max Intake Restriction: | 6kPa |
| Combustion air Flow: | 32m ³ /min |
| Fuel System | |
| 110% Standby Power Load: | 112.7L/h |
| 100% Prime Power Load: | 100.4L/h |
| 75% Prime Power Load: | 75.8L/h |
| 50% Prime Power Load: | 53.6L/h |
| Oil System | |
| Max. sump capacity | 65L |
| Cooling System | |
| Total Coolant Capacity (engine only): | 48L |
| Thermostat operation range: | 77-90°C |
| Electrical System | |
| System Voltage: | DC 24 V |
| Rated Current for Charge Alternator: | 55 A |

**GPG****Alternator Data**

| | |
|------------------------------------|--|
| Manufacturer / Type: | SDEC/ SC314F1 |
| Number of Phase: | 3 |
| Connecting Method: | 3 Phase and 4 Wires, "Y" type connecting |
| Number of Bearing: | 1 |
| Power Factor: | 0.8 |
| Protection Grade: | IP22 |
| Altitude Requirement: | ≤1000m |
| Exciter Type: | Brushless, Self-exciting |
| Insulation Class/Temperature Rise: | H/H |
| Telephone Influence Factor (TIF): | <50 |
| THF: | <2% |
| Voltage Regulation, Steady State : | ≤±1% |
| Alternator Capacity: | 450kVA |
| Alternator Efficiencies: | 94.1% |

Generating Set Data

| | |
|--|--------|
| Frequency Reduce: | ≤5% |
| Frequency Regulation, Stead State: | ≤1.5% |
| Waveform Distortion(no load): | <1.5% |
| Sudden Frequency Warp (100% Sudden Reduce): | ≤+12% |
| Sudden Frequency Warp (Sudden Increase): | ≤-10% |
| Frequency Recovery Time (100% Sudden Reduce) : | ≤5S |
| Frequency Recovery Time (Sudden Increase): | ≤5S |
| Voltage Regulation: | ≥±5% |
| Voltage Regulation, Stead State: | ≤±2.5% |
| Voltage Modulation: | 0.30% |
| Sudden Voltage Warp (100% Sudden Reduce): | ≤+25% |
| Sudden Voltage Warp (100% Sudden Increase): | ≤-20% |
| Voltage Stable Time (100% Sudden Reduce): | ≤6S |
| Voltage Stable Time (100% Sudden Increase): | ≤6S |
| Voltage Unbalance: | 1% |



GPG

Standard Control Panel



HKY-6110 control panel is fit for backpack structure and standing structure. This control panel is a panel which holds a HGM6110 made by Smartgen the professional module maker in China as its core intelligent control module. It has plenty friendly operation interface with many functions such as running parameter detecting, static, record, pre-alarm, Remote control, monitor & protection.


Options

| Engine | Alternator | Control and Power Distribution System | Others |
|--------|------------|---------------------------------------|--------|
|--------|------------|---------------------------------------|--------|

| | | | |
|----------------------------------|------------------------------------|---------------------------------------|--------------------------------------|
| ● 50°C High Temperature Radiator | ● Permanent Magnet Generator (PMG) | ● ComAp Control module | ● Daily Fuel Tank |
| ● Water Separator | ● Anti Condensation Heater | ● Deepsea Control module | ● Base Fuel Tank |
| ● Water Jacket Heater | ● Drop CT(For Paralleling) | ● Auto Transfer Switch(ATS) | ● Trailer Type |
| ● Oil Heater | | ● Battery Charge | ● Automatic Input System For Fuel |
| ● Oil Discharging Pump | | ● Manual Paralleling System | ● Maintenance Tools |
| | | ● Auto Paralleling System | ● Accesory Bag |
| | | ● Electronic Indicator for Fuel Level | ● Wind Scooper for Soundproof Canopy |

Dimension & Weight

Open Type



Overall Size LxWxH

3500mm x 1700mm x 2000mm


Weight

4500 kg

Base fuel tank capacity

Full load running for 6~8 hours

Soundproof Type



Overall Size LxWxH

4700mm x 1900mm x 2450mm

Weight

5715 kg

Base fuel tank capacity

Full load running for 6~8 hours